

BRSBVM35/2.0FHD/BRZ**2MP Breeze Series Verifocal Bullet Camera**

Camera	
Image Sensor	1/2.9" Progressive Scan SONY CMOS
Effective Pixels	1920(H) x 1080(V)
Signal System	PAL / NTSC
Min. Illumination	0.05lux@F1.2(AGC ON),0Lux with IR
Shutter Speed	1/30s – 1/50000s/AUTO
Day& Night	ICR
White Balance	ATW/AWE-SET/INDOOR/OUTDOOR/MANUAL
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D DNR
Gain Control	Auto (1~15 Optional)
Lens	
Lens	2.8 - 12 mm
Lens Type	Manual Verifocal
Mount Type	M14
Max. Aperture	F2.0
Angle of View	D: 115.6°(W)-31.9°(T) H: 97.56°(W)-27.78°(T) V:54.44°(W) - 15.72°(T)
IR LEDs	SMART IR: 24 Pcs
IR Distance	Up to 35 mtr
Aspect Ratio	16:9
Image	
Resolution	1080P@30FPS(NTSC), 1080P@25FPS(PAL)
BLC	Available
OSD	Available
OSD Control	Internal
Interface	
Video Output	1-channel BNC video output
General	
Power Supply	DC12V±10%
Power Consumption	2.8W max
Operating Temperature	-30°C ~ +55°C
Operating Humidity	Less than 95% RH (no condensation)
Ingress Protection	IP 66
Housing	METAL
Dimensions	
Weight	

Features

- 1/2.9" SONY Progressive Scan CMOS Sensor
- Resolution: 1920×1080 @ 25 / 30 fps
- 2.8-12 mm Verifocal Lens
- SMART IR, IR Distance upto 35 mtr
- Better Low light performance
- 2D DNR, DWDR, ICR
- IP66, Metal Body

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.

<http://www.bpl.in/>