

## BRSDFM30/2.0IP/BRZ(T)

## 2MP H.265 Breeze Series Dome Camera



Camera	
Image Sensor	1/2.7" Progressive CMOS
Effective Pixels	1920(H)×1080(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Supports
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Digital Noise Reduction	3D DNR
Lens	
Lens	2.8 mm
Lens Type	Fixed
Mount Type	M12
Angle of View	73°
IR LEDs	18pcs(SMD)
IR Distance	Up to 30 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Dual Streaming
Max.Resolution	1080P(1920x1080)
Video Betrate	256Kbps ~ 8Mbps
Resolution	<b>Mainstream</b> :1080P(1920x1080), 960P(1280x960), 720P(1280x720) <b>Substream</b> : VGA(640x480),QVGA(320x240)
Frame Rate	<b>Mainstream</b> :1~20fps <b>Substream</b> : 1~20fps
Image Settings	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Privacy Mask	Supports
Network	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF( Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
On-board Storage	MicroSD Card Slot supports up to 128GB
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 7W
Operating Temperature	-30~+55°C
Ingress Protection	IP 66
Dimensions	Ø100 X90mm
Weight	appr. 225g

### Features

- 1/2.7" Progressive Scan CMOS Sensor
- Resolution: 1920×1080 @ 30 fps
- H.265 Video Compression
- 2.8 mm Lens
- Smart LED, IR Distance upto 30 mtr
- Dual Stream
- Supports BLC, dWDR, Privacy Mask
- SD Card Slot
- IP66, Metal Body

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.