

## BRSDFM30/2.0IP/BRZ

## 2MP H.265 Breeze Series Dome Camera



### Features

- 1/2.9" Progressive Scan CMOS Sensor
- Resolution: 1920x1080 @ 30 fps
- H.265 Video Compression
- 2.8mm Lens
- Smart LED, IR Distance upto 30 mtr
- Triple Stream
- Supports BLC, ROI, dWDR
- **Analytics** : Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection
- IP66, Metal Body

Camera	
Image Sensor	1/2.9" Progressive CMOS
Effective Pixels	1920(H)x1080(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.1lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Supports
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Digital Noise Reduction	3D DNR
Gain Control	Auto
Defog	YES
Lens	
Lens	2.8 mm
Lens Type	Fixed
Mount Type	M12
Angle of View	73°
IR LEDs	18pcs(SMD)
IR Distance	Up to 30 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Triple Streaming
Max.Resolution	1080P(1920x1080)
Video Betrate	8Kbps ~ 8Mbps
Resolution	<b>Mainstream:</b> 1080P(1920x1080), 960P(1280x960), 720P(1280x720) <b>Substream:</b> 960P(1280x960), VGA(640x480), QVGA(320x240) <b>Mobile Stream:</b> VGA(640x480), QVGA(320x240)
Frame Rate	<b>Mainstream</b> :1~30fps <b>Substream</b> : 1~30fps <b>Mobile Stream:</b> 1~30fps
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Region of Interest (ROI)	Supports
Privacy Mask	Supports
Network	
Alarm Detection	Motion Detection
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF( Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 7W
Operating Temperature	-30~+55°C
Ingress Protection	IP 66
Dimensions	Ø90 X 85mm
Weight	appr. 378g

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.