

BRSDFM30/5.0IP/BRZ

5MP H.265 Breeze Series IR Dome Camera



Camera	
Image Sensor	1/2.7" Progressive CMOS
Effective Pixels	5MP 2592(H)×1944(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.05lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Supports
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Lens	
Lens	3.6 mm
Lens Type	Fixed
Angle of View	88°
IR LEDs	18pcs(SMD)
IR Distance	Up to 30 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Dual Streaming
Max.Resolution	5MP 2592(H)×1944(V)
Video Betrate	256Kbps ~ 8Mbps
Resolution	Main Stream: 5MP(2592×1944), 4MP(2592×1520), 3MP(2048×1520), 1080P(1920×1080), 960P(1280×960), 720P(1280×720) Sub Stream: VGA(640×480),QVGA(320×240)
Frame Rate	Main Stream :1~15fps Sub Stream : 1~15fps
Image Settings	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Privacy Mask	Supports
Network	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF(Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 7W
Operating Temperature	-30~+55°C
Ingress Protection	IP 66
Dimensions	Ø100 X90mm
Weight	appr. 225g

Features

- 1/2.7" Progressive Scan CMOS Sensor
- Resolution: 2592×1944 @ 15 fps
- H.265 Video Compression
- 3.6mm Lens
- Smart LED, IR Distance upto 30 mtr
- Dual Stream
- dWDR, BLC, Support Privacy Mask
- IP66, Metal Body

Product Specifications are subject to change without prior notice. The images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.