

BTDDFM30/2.0IP/INT(L)


2MP H.265 Intelligent Lite Series IR Dome Camera



Features

- 1/2.7" CMOS Sensor
- Resolution: 1920x1080 @ 30 fps
- H.265 Video Compression
- 2.8 mm Lens
- Smart LED, IR Distance upto 30 mtr
- Dual Stream
- WDR, 3DDNR, HLC, Smart Defog
- **Analytics** : Tripwire/Perimeter
- **Alarm**: Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
- IP66, Metal Body

Dimensions



Camera	
Image Sensor	1/2.7" CMOS
Core Processor	ARM9 Architecture
Operating System	Embedded Linux
Signal System	PAL/NTSC
Min. Illumination	Color: 0.05Lux B/W: 0.01Lux
Shutter Time	1s to 1/100,000s
Lens	2.8 mm
Wide Dynamic Range	100dB
Digital Noise Reduction	3D DNR
Compression Standard	
Video Compression	S+265 / H.265 / H.264 / M-JPEG
Video Bit Rate	32Kbps ~ 16Mbps
Image	
Max. Image Resolution	1920 x 1080
Frame Rate	PAL: 1080p@25fps, 960p@25fps, 720p@25fps, D1@25fps NTSC: 1080p@30fps, 960p@30fps, 720p@30fps, D1@30fps
Stream	Mainstream: 1080P (1920*1080) Substream: 4CIF (704*480)
Image Settings	Brightness, Saturation, Contrast, Flip Mode Adjustable by Client Software or Web Browser
HLC	Yes
Smart Defog	Yes
OSD	16×16, 32×32, 48×48 Size Letters Such as Week, Date, Time, Total 1 Regions
Network	
Browser	Built-in Web Server
NTP	Yes
Video Analytics	Tripwire / Perimeter
Alarm Trigger	Motion Detection / IP Conflict / MAC Conflict / Mask Alarm
Protocols	TCP / UDP / HTTP / MULTICAST / UPnP / DHCP / DDNS / FTP / NTP / RTSP / SMTP
User Permission	4 Level / 8 Users
System Compatibility	ONVIF (Profile S), P2P
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
General	
Language	English, Simplified Chinese, Traditional Chinese, Spanish, Italian, Korean, Turkish, Russian, Thai, Polish, French
Operating Conditions	-35°C~60°C, 0~95% RHG
Power Supply	DC 12 V ± 25%, POE
Power Consumption	Max. 3W(IR OFF) (ICR Instant Switch 5.5W)
Impact Protection	IP 66
IR Range	20-30m
Dimensions	115mm(diameter) * 97mm(height)
Weight	0.6KG

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.