

BRSBMM45/5.0IP/BRZ

5MP H.265 Motorized IR Bullet Camera



Features

- 1/2.9" Progressive CMOS Sensor
- Resolution: 5MP 2592×1944 @ 30 fps
- H.265 Video Compression
- 2.8-12 mm Motorized Lens
- Smart IR, IR Distance upto 45 mtr
- Triple Stream
- BLC, ROI, Privacy Mask, Digital WDR
- SD Card Slot, Audio I/O, Alarm I/O
- **Analytics** : Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection
- **Alarm**: Motion Detection
- IP66, Metal Body

Camera	
Image Sensor	1/2.9" Progressive CMOS
Effective Pixels	2592(H)×1944(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.01lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Supports
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Digital Noise Reduction	3D DNR
Gain Control	Auto
Defog	YES
Lens	
Lens	2.8 ~ 12 mm
Lens Type	Motorized Verifocal
Angle of View	87 ~ 28°
IR LEDs	40pcs(SMD)
IR Distance	Up to 45 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Triple Streaming
Max.Resolution	5MP (2592×1944)
Video Betrate	8Kbps ~ 8Mbps
Resolution	Main Stream : 5MP(2592×1944), 4MP(2592×1520), 3MP(2048×1520), 1080P(1920×1080), 960P(1280×960), 720P(1280×720) Sub Stream : 720P(1280×720), VGA(640×480), QVGA(320×240) Mobile Stream : VGA(640×480), QVGA(320×240)
Frame Rate	Main Stream :1~20fps Sub Stream : 1~20fps Mobile Stream : 1~20fps
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Region of Interest (ROI)	Supports
Privacy Mask	Supports
Network	
Alarm Detection	Motion Detection
Video Analytics	Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Cross Counting
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF(Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
Audio	1 Ch Audio In, 1 Ch Audio Out
Alarm	1 Ch Alarm In, 1 Ch Alarm Out
BNC Output	1 Ch BNC output
Reset Button	Available
On-board Storage	Micro SD/SDHC/SDXC slot supports Max 128GB
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 7W
Operating Temperature	-30~+55°C
Ingress Protection	IP 66
Dimensions	Ø88 X 242mm
Weight	appr. 881g

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.