

BRSBMM45/8.0IP/BRZ

8MP H.265 Motorized IR Bullet Camera



| Camera | |
|--------------------------|---|
| Image Sensor | 1/2.5" Progressive CMOS |
| Effective Pixels | 3840(H)×2160(V) |
| Signal System | PAL / NTSC |
| Operating System | Embedded Linux |
| Min. Illumination | Color 0.01lux @ F1.2(AGC ON); B/W 0 lux @ IR ON |
| Shutter Speed | 1/5 ~ 1/20000s |
| Slow Shutter | Supports |
| Day& Night | IR cut filter with auto switch |
| Wide Dynamic Range | dWDR |
| Digital Noise Reduction | 3D DNR |
| Gain Control | Auto |
| Defog | YES |
| Lens | |
| Lens | 3.3 ~ 12 mm |
| Lens Type | Motorized Verifocal |
| Angle of View | 114 ~ 36° |
| IR LEDs | 40pcs(SMD) |
| IR Distance | Up to 45 Mtr |
| Image | |
| Video Compression | H.265/H.264 |
| Streaming Capability | Triple Streaming |
| Max.Resolution | 8MP (3840x2160) |
| Video Betrate | 8Kbps ~ 8Mbps |
| Resolution | Main Stream: 8MP (3840x2160), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), Sub Stream: 1080P(1920x1080), 720P(1280x720), VGA(640x480), QVGA(320x240) Mobile Stream: VGA(640x480), QVGA(320x240) |
| Frame Rate | Main Stream: 1~20fps Sub Stream: 1~20fps Mobile Stream: 1~20fps |
| Image Settings | Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable |
| BLC | Supports |
| Region of Interest (ROI) | Supports |
| Privacy Mask | Supports |
| Network | |
| Alarm Detection | Motion Detection |
| Video Analytics | Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection, Pedestrian Detection, Cross Counting |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP |
| System Compatibility | ONVIF(Ver 2.6) |
| Interface | |
| Communication Interface | 1-ch RJ45 10M / 100M Ethernet Interface |
| Audio | 1 Ch Audio In, 1 Ch Audio Out |
| Alarm | 1 Ch Alarm In, 1 Ch Alarm Out |
| BNC Output | 1 Ch BNC output |
| Reset Button | Available |
| On-board Storage | Micro SD/SDHC/SDXC slot supports Max 128GB |
| General | |
| Language | English, Chinese |
| Power Supply | DC 12V/POE |
| Power Consumption | ≤ 7W |
| Operating Temperature | -30~+55°C |
| Ingress Protection | IP 66 |
| Dimensions | Ø88 X 242mm |
| Weight | appr. 881g |

Features

- 1/2.5" Progressive CMOS Sensor
- Resolution: 8MP 3840×2160 @ 30 fps
- H.265 Video Compression
- 3.3-12 mm Motorized Lens
- Smart IR, IR Distance upto 45 mtr
- Triple Stream
- BLC, ROI, Privacy Mask, Digital WDR
- SD Card Slot, Audio I/O, Alarm I/O
- **Analytics** : Perimeter Intrusion Detection, Line Crossing Detection, Stationary Object Detection
- **Alarm**: Motion Detection
- IP66, Metal Body

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.