

BRSFFM10/5.0IP/SPL

5MP H.265 IR Fisheye Camera



Features

- 1/2.9" Progressive CMOS Sensor
- Resolution: 2160×2160
- H.265 Video Compression
- 1.1 mm Lens, Angle of View 360°
- Smart IR, IR Distance upto 10 mtr
- Triple Stream
- BLC, ROI, Digital WDR
- SD Card Slot, Audio I/O, Alarm I/O
- IP64, Metal Body

Camera	
Image Sensor	1/2.9" Progressive CMOS
Effective Pixels	5MP 2160(H)×2160(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.1lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Lens	
Lens	1.1 mm
Lens Type	Fixed
Angle of View	360°
IR LEDs	3pcs(SMD)
IR Distance	Up to 10 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Triple Streaming
Max.Resolution	5MP 2160(H)×2160(V)
Video Betrate	8Kbps ~ 8Mbps
Resolution	Main Stream: 5MP (2160×2160), 1520x1520, 1080x1080, 720x720 Sub Stream: 720x720, 480x480, 240x240 Mobile Stream: 480x480, 240x240
Frame Rate	Main Stream: 1~20fps Sub Stream: 1~20fps Mobile Stream: 1~20fps
Image Settings	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Region of Interest (ROI)	Supports
Network	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF(Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
Audio	Supports
Alarm	Supports
BNC Output	Supports
Reset Button	Available
On-board Storage	Micro SD/SDHC/SDXC slot supports Max 128GB
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 5W
Operating Temperature	-30~+55°C
Ingress Protection	IP 64
Dimensions	Ø120*55mm
Weight	appr. 400g

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.