

BSUBVM70/12.0IP/4K

12.0MP Motorized IR Bullet Camera



Camera	
Image Sensor	1/1.7" Progressive Scan CMOS
Effective Pixels	4000(H)×3000 (V)
Scanning System	Progressive
Electronic Shutter	1/5-1/20000s
Min. illumination	Color:0.009Lux@(F1.2,AGC ON) B/W:0Lux@(IR LED ON)
S/N Ratio	55dB
Pan/Tilt/Rotation Range	Pan:0°~360°, Tilt:0°~90°, Rotation:0°~360°
Lens	
Focal Length	4.1 ~ 12.8mm
Lens Type	Manual Verifocal
Iris	P-Iris
Angle of View	98° ~ 34.5°
Close Focus Distance	1m
IR Range	Up to 70m
IR On/Off Control	Auto/ Manual
IR LEDs	8pcs
Video	
Compression	H.265,H.264,MJPEG
Max. Resolution	12MP(4000×3000)
Streaming	Main Stream: 4000×3000 @ 20fps, 4096×2160 / 3840×2160 / 1920×1080 / 1280×720 @25/30fps Sub Stream: D1 / VGA / 640×360 / CIF @ 25/30fps Third Stream: VGA / CIF / QVGA @25/30fps
Bit Rate Control	CBR/VBR
Bit Rate	Main Stream: 500kbps~16000kbps Sub Stream: 100kbps~6000kbps Third Stream: 100kbps~3000kbps
Day/Night	ICR
Image Enhancement	HLC / Defog / dWDR
White Balance	Support
Gain Control	Auto/Manual
Noise Reduction	2D/3D DNR
EIS	Support
Region of Interest	Support
Privacy Masking	Support
Motion Detection	Support
Audio	
Compression	G.711 ,RAW_PCM
Bit Rate	64kbps (G.711), 128kps (RAW_PCM)
Network	
Protocols	IPv4/IPv6, 802.1x, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/ RTP, PPPoE, SMTP, DNS, UPnP, FTP, APR, SNMP
Streaming Method	Unicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox
System Compatibility	ONVIF
Intelligence	
IVS	Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed ,Converse, Illegal Parking, Signal Bad
Interface	
Ethernet	1-ch Ethernet (10/100 Base-T) RJ-45 Connector
Audio Interface	1ch Audio In,1ch Audio Out
Alarm	1ch Alarm In,1ch Alarm Out
RS485	Support
BNC Output	Support
Reset Button	Support
On-board Storage	Micro SD/SDHC slot supports Max 128GB
General	
Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French
Power Supply	DC12V/POE
Power Consumption	5W(IR LED OFF),8W (IR LED ON)
Operating Temperature	Starting Temperature: -30°C ~ 60°C (-22°F ~ 140°F) Working Temperature: -40°C ~ 60°C (-40°F ~ 140°F)
Operating Humidity	Less than 90% RH
Ingress Protection	IP67
Casing	Metal
Dimensions	φ110×375.5mm
Net Weight	1680g

Features

- 1/1.7" Progressive Scan CMOS Sensor
- Resolution: 4K 4000X3000 @ 20fps
- H.265 Video Compression
- 4.1-12.8 mm Motorized Lens
- Smart IR, IR Distance upto 70 mtr
- Triple Stream
- 3D DNR, dWDR, ICR, ROI, Defog, HLC, Corridor mode ,DIS
- 1ch Audio In,1ch Audio Out, 1ch Alarm In,1ch Alarm Out, RS485 port, BNC Output
- Micro SD/SDHC/SDXC slot supports Max 128GB
- **Alarm:** Perimeter, Single Virtual Fences, Double Virtual Fences, Loiter, Multi Loiter, Object Left, Object Removed, Abnormal Speed, Converse, Illegal Parking, Signal Bad, Motion Detection, Network disconnect, Disk alarm, I/O alarm
- IP66, Metal Body

Dimensions

