

BRSDFM30/2.0IP/SUP

2MP H.265 Super Series Dome Camera



Camera	
Image Sensor	1/2.7" Progressive CMOS
Effective Pixels	1920(H)×1080(V)
Signal System	PAL / NTSC
Operating System	Embedded Linux
Min. Illumination	Color 0.1lux @ F1.2(AGC ON); B/W 0 lux @ IR ON
Shutter Speed	1/5 ~ 1/20000s
Slow Shutter	Supports
Day& Night	IR cut filter with auto switch
Wide Dynamic Range	dWDR
Digital Noise Reduction	3D DNR
Gain Control	Auto
Defog	YES
Lens	
Lens	3.6 mm
Lens Type	Fixed
Mount Type	M12
Angle of View	88°
IR LEDs	18pcs(SMD)
IR Distance	Up to 30 Mtr
Image	
Video Compression	H.265/H.264
Streaming Capability	Dual Streaming
Max.Resolution	1080P(1920x1080)
Video Betrate	256Kbps ~ 8Mbps
Resolution	Mainstream: 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substream: VGA(640x480), QVGA(320x240)
Frame Rate	Mainstream : 1~20fps Substream : 1~20fps
Image Settings	Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Supports
Region of Interest (ROI)	Supports
Privacy Mask	Supports
Network	
Alarm Detection	Motion Detection
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
System Compatibility	ONVIF(Ver 2.6)
Interface	
Communication Interface	1-ch RJ45 10M / 100M Ethernet Interface
General	
Language	English, Chinese
Power Supply	DC 12V/POE
Power Consumption	≤ 7W
Operating Temperature	-30~+55°C
Ingress Protection	IP 66
Dimensions	Ø63 X115mm
Weight	appr. 225g

Features

- 1/2.7" Progressive Scan CMOS Sensor
- Resolution: 1920×1080 @ 20 fps
- H.265 Video Compression
- 3.6mm Lens
- Smart LED, IR Distance upto 30 mtr
- Dual Stream
- dWDR, BLC, Support Privacy Mask
- IP66, Metal Body

Product Specifications are subject to change without prior notice. The Images shown are only indicative, actual product may vary. Product features are tested under ideal conditions.

<http://www.bpl.in/>